

CONTINUATION SHEET	Reference No. of Document Being Continued PIIN/SIIN W56HZV-04-P-1257 MOD/AMD P00001	Page 2 of 4
---------------------------	---	--------------------

Name of Offeror or Contractor: UNITED DEFENSE LP

SUPPLEMENTAL INFORMATION

1. The purpose of this modification is to clarify the packaging requirements listed in clause 14.
2. In clause 14, Packaging Requirement (Special Packaging Instructions), the instruction number listed at (a)(4) should show SPI #AK 14222573, not ASTM3951.
3. All other terms and conditions of this order remain the same.
4. The contractor shall receive an email with the SPI attached, this SPI was a part of the TDP during the solicitation period.

*** END OF NARRATIVE A 002 ***

CONTINUATION SHEET**Reference No. of Document Being Continued****Page 3 of 4**

PIIN/SIIN W56HZV-04-P-1257

MOD/AMD P00001

Name of Offeror or Contractor: UNITED DEFENSE LP

CONTRACT CLAUSES

<u>Status</u>	<u>Regulatory Cite</u>	<u>Title</u>	<u>Date</u>
---------------	------------------------	--------------	-------------

1 CHANGED	52.211-4515 (TACOM)	PACKAGING REQUIREMENT (SPECIAL PACKAGING INSTRUCTIONS)	MAR/2004
-----------	------------------------	--	----------

(a) Military preservation, packing, and marking for this contract/order shall be accomplished in accordance with the specific requirements identified below, all the applicable requirements of, MIL-STD-2073-1, Revision D, Dated 15 Dec 1999 and Notice 1, dated 10 May 2002, and the Special Packaging Instruction, see below.

(1) LEVEL OF PRESERVATION: Military

(2) LEVEL OF PACKING: B

(3) QUANTITY PER UNIT PACKAGE: 001

(4) SPECIAL PACKAGING INSTRUCTION NUMBER: AK14222753

a. REVISION AS LISTED ON TDPL

b. DATE OF REVISION AS LISTED ON TDPL

(b) Unitization: Shipments of identical items going to the same destination shall be palletized if they have a total cubic displacement of 50 cubic feet or more unless skids or other forklift handling features are included on the containers. Pallet loads must be stable, and to the greatest extent possible, provide a level top for ease of stacking. A palletized load shall be of a size to allow for placement of two loads high and wide in a conveyance. The weight capacity of the pallet must be adequate for the load. The preferred commercial expendable pallet is a 40 x 48 inch, 4-way entry pallet although variations may be permitted as dictated by the characteristics of the items being unitized. The load shall be contained in a manner that will permit safe handling during shipment and storage

(c) Marking:

(1) In addition to any special markings called out on the SPI, all unit packages, intermediate packs, exterior shipping containers, and, as applicable, unitized loads shall be marked in accordance with MIL-STD-129, Revision P, Dated 15 Dec 2002, including bar coding. The contractor is responsible for application of special markings as discussed in the Military Standard regardless of whether specified in the contract/order or not. Special markings include, but are not limited to, Shelf-life markings, structural markings, and transportation special handling markings. The marking of pilferable and sensitive materiel will not identify the nature of the materiel.

(2) Contractors and vendors shall apply identification and address markings with bar codes in accordance with this standard. For shipments moving to overseas locations and for mobile deployable units, the in-the-clear address must also include the host country geographic address and the APO/FPO address. A Military Shipment Label (MSL) is required for all shipments except contractor to contractor. The MSL will include both linear and 2D bar codes per the standard. DVD shipment documentation must also be marked with additional bar codes. The DD Form 250 or the commercial packing list shall have additional issue/receipt bar coding applied as per Direct Vendor Delivery Shipments in the standard (except for deliveries to DLA Distribution Depots, e.g. New Cumberland, San Joaquin, Red River, Anniston). . Packing lists are required in accordance with the Standard, see paragraph 5.3.

(3) Contractor to contractor shipments shall have the address markings applied to the identification marked side of the exterior shipping container or to the unitized load markings. The following shall be marked "FROM: name and address of consignor and TO: name and address of consignee".

(4) Military Shipping Label: : Military Shipment Labels(MSLs) may be created using commercially available programs. These commercial programs can generate a MIL-STD-129 and Defense Transportation Regulation compliant MSLs and package labels. For example, the EasyForm MSL at <http://www.easysoftcorp.com/products/Software/MSL.html>. Insure that the ship to and mark for in-the-clear delivery address is complete including: consignees name, organization, department name, office, building, room, street address, city, state, country code, & DODAAC.

(d) Heat Treatment and Marking of Wood Packaging Materials: Boxes/pallets and any wood used as inner packaging made of non-manufactured wood shall be heat-treated. All non-manufactured wood used in packaging shall be heat treated to a core temperature of 56 degrees Celsius for a minimum of 30 minutes. The box/pallet manufacturer and the manufacturer of wood used as inner packaging shall be affiliated with an inspection agency accredited by the board of review of the American Lumber Standard Committee. The box/pallet manufacturer and the manufacturer of wood used as inner packaging shall ensure traceability to the original source of heat treatment. Each box/pallet shall be marked to show the conformance to the International Plant Protection Convention Standard. The quality mark shall be placed on both ends of the outer packaging, between the end cleats or end battens; on two sides of the pallet. Foreign manufacturers shall have the heat treatment of non-manufactured wood products verified in accordance with their National Plant Protection Organizations compliance program.

CONTINUATION SHEET	Reference No. of Document Being Continued	Page 4 of 4
	PIIN/SIIN W56HZV-04-P-1257	MOD/AMD P00001

Name of Offeror or Contractor: UNITED DEFENSE LP

(e) Hazardous Materials(As applicable):

(1) Hazardous Materials is defined as a substance, or waste which has been determined by the Secretary of Transportation to be capable of posing an unreasonable risk to health, safety, and property when transported in commerce and which has been so designated. (This includes all items listed as hazardous in Titles 29, 40 and 49 CFR and other applicable modal regulations effective at the time of shipment.)

(2) Unless otherwise specified, packaging and marking for hazardous material shall comply with the requirements herein for the mode of transport and the applicable performance packaging contained in the following documents:

International Air Transport Association (IATA) Dangerous Goods Regulations

International Maritime Dangerous Goods Code (IMDG)

Code of Federal Regulations (CFR) Title 29, Title 40 and Title 49

Joint Service Regulation AFJMAN24-204/TM38-250/NAVSUPPUB 505/MCO

P4030.19/DLAM 4145.3 (for military air shipments).

(3) If the shipment originates from outside the continental United States, the shipment shall be prepared in accordance with the United Nations Recommendations on the Transport of Dangerous Goods in a manner acceptable to the Competent Authority of the nation of origin and in accordance with regulations of all applicable carriers.

A Product Material Safety Data Sheets (MSDS) is required to be included with every unit pack and intermediate container and shall be included with the packing list inside the sealed pouch attached to the outside of the package.

(f) This SPI has been validated and the method of preservation/packing has proven successful in meeting the needs of the military distribution system, including indeterminate storage and shipment throughout the world. Special instructions and/or tailoring of the SPI is detailed in the Supplemental Instructions below. A prototype package is required to validate the sizes and fit requirements of the SPI. Minor dimensional and size changes are acceptable provided contractor provides the PCO and ACO with notification 60 days prior to delivery. Any design changes or changes in the method of preservation that provide a cost savings without degrading the method of preservation or packing or affecting the serviceability of the item will be considered and responded to within 10 days of submission to PCO and ACO. Government reserves the right to require testing to validate alternate industrial preservation methods, materials, alternate blocking, bracing, cushioning, and packing.

(f) SUPPLEMENTAL INSTRUCTIONS: NONE

[End of Clause]